

BODY 900 CAVITY WAX

Technical Data Sheet No 712

General Technical Description

Special anticorrosive cavity wax oil treatment with sound deadening properties

It remains elastic and it is adhered perfectly

Provides excellent underbody protection

Dries quickly

Penetrates easily

Resistant to high temperature

Suitable for application after the paint procedure

Product Application:



Shake well before using: 2-3min



Always close tin after use

Alwavs wear

this TDS

protective equipment

Follow the application

instructions mentioned in



Application with spray gun: Pressure 5-6 bar (73-87 psi)



Drving time 2-6h /23°C (73°F) depending on thickness



Protect from humidity and freeze



Specific Gravity: 1.02 g/cm³

Flash Point:

5°C (41°F)

Surface

vehicle

All closed parts (doors, bonnet,

External underbody parts of the

running boards (chassis))

Solid Content (No thinner): 56% Weight

VOC (2004/42/EC)

This product is a special refinish product based on its ingredients and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in ready for use form of this product is 415 g/L. 2004/42/IIB(e)(840)415

Theoretical Coverage: 4-5 m²/l at 100micron (4 mil) dry film thickness

Cleaning of equipment:

Clean after final use with: 740 ACRYL NORMAL THINNER / 767 ECO THINN NITRO THINNER

Pretreatment / Cleaning of substrate



Clean substrate using a soft cloth and 770 ANTISIL NORMAL /771 ANTISIL FAST DEGREASER

Make sure the surface is first wiped then air dried.



Make sure you always use appropriate face protection and good ventilation

Remarks:

• Allow for additional time for combi spray booths to reach the desired temperature

• Best results when used with HB BODY PRODUCTS.

• It can be used by countries that do not adopt the VOC legislation as well.

Storage shelf life:

 Store in a cool place +5°C - +25°C (+41°F - +77°F) and use within 12 months for best results. Guaranteed shelf life of 24 months in unused original containers.

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Issue 4/2019, March 2019

